Flat suction cup (round)

SUF 5 NBR-ESD-55 M5-IG

Part no..:10.01.01.14239


https://www.schmalz.ru/10.01.01.14239

Flat suction cup (round) for process safe handling of smooth or slightly rough surfaces



- Size: 5
- Suction cup material: Nitrile rubber NBR-ESD
- Material hardness [Shore A]: 55 Shore A
- Vacuum connection: M5-F

Design Data



Attribute	Value
Dmax(S)	5.70 mm
Ds	5 mm
dn	1.80 mm
G1	M5-F
H	14.20 mm
LG1	5.50 mm
SW1	8 mm
Z (Stroke)	0.50 mm

Technical Data

Attribute	Value
Suction force (-600mbar)	0.90 N
Pull-off force	0.90 N
Volume	0.01 cm^3
Curve radius (min) (convex)	8 mm
Hose diameter (rec.) d	2 mm
Size	5
Suction cup material	Nitrile rubber NBR-ESD
Material hardness [Shore A]	55 Shore A

Contact Schmalz
OOO Schmalz | Mozhayskoe highway 165, bdg1, 121596 Moscow, Russia | +7 495 9671248 | post@ruschmalz.ru

Flat suction cup (round)

SUF 5 NBR-ESD-55 M5-IG

Part no..:10.01.01.14239

https://www.schmalz.ru/10.01.01.14239

Weight	1.10 g
Product family	SUF
Number of folds	0

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m

Spare parts



SC 020 M5-IG

Part no..:10.01.06.04306

Connection geometry: 020
Vacuum connection: M5-F
Fitting length: 8.7 mm
Nominal diameter dn: 1.8 mm



SUF 5 NBR-ESD-55 SC020

Part no..:10.01.01.14022

Size: 5
Suction cup material: Nitrile rubber NBR-ESD
Material hardness [Shore A]: 55 Shore A