Bellows suction cup (round)

SAB 125 NBR-60 G1/4-IG

Part no..:10.01.06.00854


https://www.schmalz.ru/10.01.06.00854

Bellows suction cup (round) for very dynamic handling of smooth and oily workpieces



- Size: 125
- Suction cup material: Nitrile rubber NBR
- Material hardness [Shore A]: 60 Shore A
- Nipple material: Nickel plated
- Connection: G1/4-IG
- Number of folds: 1.5

Design Data



Attribute	Value
dn	6 mm
D1	94 mm
Dmax(S)	135 mm
Ds	126 mm
G1	G1/4"-F
H	72.80 mm
LG1	20 mm
SW1	22 mm
Z (Stroke)	32 mm

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

Technical Data

Attribute	Value
Suction force (-600mbar)	250 N
Pull-off force	558 N
Lateral force	410 N
Lateral force (oily surface)	335 N
Volume	220 cm^3
Curve radius (min) (convex)	140 mm
Hose diameter (rec.) d	9 mm

Contact Schmalz
OOO Schmalz | Mozhayskoe highway 165, bdg1, 121596 Moscow, Russia | +7 495 9671248 | post@ruschmalz.ru

Bellows suction cup (round)

SAB 125 NBR-60 G1/4-IG

Part no..:10.01.06.00854

https://www.schmalz.ru/10.01.06.00854

Size	125
Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	60 Shore A
Weight	183.10 g
Product family	SAB
Number of folds	1.50

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Lateral force: The specified lateral forces are values measured at a vacuum of -0.6 bar with a dry or oily, smooth, flat workpiece surface. Depending on the workpiece surface and its quality, the actual values may deviate from these values Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m