

Connection set

SET VC-MPL G1/2-IG

Part no...:10.01.27.01732

<https://www.schmalz.ru/10.01.27.01732>

Home > Vacuum Clamping Technology > Clamping Equipment for Metal and Plastic Processing > Modular Clamping System MPL-ISST-SFM for Metal and Plastics Machining > SET VC-MPL G1/2-IG

Connection set for hose connection



Construction use: Matrix-Plate

Connection: G1/2"-F

Design Data



Spare parts

Contact Schmalz

OOO Schmalz | Mozhayskoe highway 165, bldg1, 121596 Moscow, Russia | +7 495 9671248 | post@ruschmalz.ru

Connection set

SET VC-MPL G1/2-IG

Part no...:10.01.27.01732

<https://www.schmalz.ru/10.01.27.01732>



VRS-SB G1/4-AG ISKT O-Ring

Part no...:10.08.06.00044

Thread G1: G1/4"-M

Material: Brass

Surface: nickel plated



HSV 12 3/2 G1/2-IG

Part no...:10.05.07.00036

Nominal size: 12 mm

Function: 3/2-way valve

Thread G1: G1/2"-F

Pressure range (operating pressure): -0.95 ... 10.00 bar



VSL 10-7 PU MI-TR

Part no...:10.07.09.00084

External diameter D: 10 mm

Internal diameter d: 7 mm

Length max.: 50 m

Material hose: PU

Bending radius min.: 60 mm

Pressure range (operating pressure): -0.95 ... 10.00 bar

Operating temperature: -40 ... 85 °C

Connection set

SET VC-MPL G1/2-IG

Part no...:10.01.27.01732

<https://www.schmalz.ru/10.01.27.01732>



ST G1/2-AG 13 MS-V

Part no...:10.08.03.00162

Thread G1: G1/2"-M

Hose diameter (rec.) d: 13 mm

Material: Brass

Surface: nickel plated

Length L: 6 mm

Nominal diameter dn: 11 mm



ST G3/4-AG 25 MS-V

Part no...:10.08.03.00223

Thread G1: G3/4"-M

Hose diameter (rec.) d: 25 mm

Length L: 6 mm

Material: Brass

Surface: nickel plated

Nominal diameter dn: 20 mm



STV-W G1/4-AG 10

Part no...:10.08.02.00254

Thread G1: G1/4"-M

Hose diameter: 10 mm

Material: Nickel plated

Operating temperature: -20 ... 80 °C

Length L: 27.2 mm

Connection set

SET VC-MPL G1/2-IG

Part no...:10.01.27.01732

<https://www.schmalz.ru/10.01.27.01732>



STV-GE G1/4-AG 10

Part no...:10.08.02.00251

Thread G1: G1/4"-M

Hose diameter: 10 mm

Material: Brass

Operating temperature: -20 ... 80 °C

External diameter D: 16.5 mm

Length L: 23.4 mm