

Plug union, elbow

STV-WF G3/8-AG 8

Part no.:10.08.02.00234

<https://www.schmalz.ru/10.08.02.00234>

Home > Screw in Push Fittings > STV-WF G3/8-AG 8

Push-in Fitting, swivelling and lockable



Thread G1: G3/8"-M


Hose diameter: 8 mm

Material: Nickel plated

Operating temperature: -10 ... 70 °C

Length L: 26.7 mm

Design Data



Attribute	Value
d	8 mm
G1	G3/8"-M
dn	9.40 mm
D1	14.30 mm
H	10 mm
H1	24.90 mm
L	26.70 mm
L1	37.60 mm
LG1	6.70 mm
SW1	22 mm
SW3	22 mm

Technical Data

Attribute	Value
Hose type	Hose D = 8 d = 6
Hose type	8-6
Material	Nickel plated
Pressure range (operating pressure)	-0.95 ... 15.00 bar
Operating temperature	-10 ... 70 °C
Weight	76 g
Product family	STV

Contact Schmalz

OOO Schmalz | Mozhayskoe highway 165, bldg1, 121596 Moscow, Russia | +7 495 9671248 | post@ruschmalz.ru

Plug union, elbow

STV-WF G3/8-AG 8

Part no.:10.08.02.00234

<https://www.schmalz.ru/10.08.02.00234>

Accessories



VSL 8-6 PE BL

Part no.:10.07.09.00015

External diameter D: 8 mm

Internal diameter d: 6 mm

Length max.: 100 m

Material hose: PE

Pressure range (operating pressure): bar

Operating temperature: °C



VSL 8-6 PU MI-TR

Part no.:10.07.09.00003

External diameter D: 8 mm

Internal diameter d: 6 mm

Length max.: 500 m

Material hose: PU

Bending radius min.: 45 mm

Pressure range (operating pressure): -0.95 ... 10.00 bar

Operating temperature: -35 ... 60 °C