

Vacuum hose (meter)

VSL 71-60 PVC-DS GR

Part no.:10.07.09.00012

<https://www.schmalz.ru/10.07.09.00012>

Home > Vacuum Technology for Automation > Vacuum Components > Filters and Connections > Hoses and Connections > Vacuum / Compressed Air Hoses VSL > VSL 71-60 PVC-DS GR

Hose for vacuum and compressed-air systems



External diameter D: 71 mm

Internal diameter d: 60 mm

Length max.: 25 m

Material hose: PVC with wire spiral

Bending radius min.: 110 mm

Pressure range (operating pressure): -0.73 ... 1.27 bar

Operating temperature: -20 ... 70 °C

Design Data



Attribute	Value
d	60 mm
D	71 mm

Technical Data

Attribute	Value
Hose type	71-60
Pressure range (operating pressure)	-0.73 ... 1.27 bar
Operating temperature	-20 ... 70 °C
Bending radius min.	110 mm
Length max.	25 m
Weight/Meter	1190 g/m
Weight/Meter	1.19 kg/m
Material hose	PVC with wire spiral

Contact Schmalz

OOO Schmalz | Mozhayskoe highway 165, bdg1, 121596 Moscow, Russia | +7 495 9671248 | post@ruschmalz.ru

Vacuum hose (meter)

VSL 71-60 PVC-DS GR

Part no.:10.07.09.00012

<https://www.schmalz.ru/10.07.09.00012>

Product family

VSL

Note: Operating pressure: In reference to media and ambient temperature of + 20 °C Min. bending radius: Referred to the inner side of the hose bend in a static state Max. length: Please indicate the tube length when placing the order!

Accessories



SSD 65-70 ST-VZ

Part no.:10.07.10.00098

Clamping range: 65.0 ... 70.0 mm

Material: Steel

Surface: galvanised