

Spring plunger

FSTIm M5-IG M5-IG A 5 VG-CO

Part no...:10.01.02.01620

<https://www.schmalz.ru/10.01.02.01620>

Home > Vacuum Technology for Automation > Vacuum Components > Mounting Elements > Spring Plungers > Spring Plungers FSTIm > FSTIm M5-IG M5-IG A 5 VG-CO

Spring plunger with internal damping spring and height compensation




Suction cup connection: M5-F

Shape: Axial vacuum guide

Spring stroke Z: 5 mm

Shape mounting elements: rotation lock /conductive



dn 2 mm

G1 M5-F

G2 M5-F

G3 M10x1-M

H 42.40 mm

H2 14 mm

LG1 4.50 mm

LG2 4.50 mm

LG3 20 mm

SW1 14 mm

SW2 8 mm

Z (Stroke) 5 mm

Recommendation: Avoid maximum plunger stroke Z during continuous operation to extend service life Ensure that the hose guide is free from distortion

Shape mounting elements	rotation lock /conductive
Spring rate	0.06 N/mm
Spring pretension	0.50 N
Spring force, center	0.64 N

Contact Schmalz

OOO Schmalz | Mozhayskoe highway 165, bldg1, 121596 Moscow, Russia | +7 495 9671248 | post@ruschmalz.ru

Spring plunger


FSTIm M5-IG M5-IG A 5 VG-CO

Part no.:10.01.02.01620

<https://www.schmalz.ru/10.01.02.01620>

Vertical load	15 N
Horizontal load	10 N
Weight	17.50 g
Operating temperature	0 ... 80 °C
Product family	FSTIm

Note: Spring force: Referred to 50 % of operating stroke Vertical loading: Maximum static loading Horizontal load: The specification of the horizontal load refers to the lower edge of the plunger with extended spring. It is a maximum static stress and it impairs the spring compression and extension in horizontal position.



VSL 4-2.5 PU BL SO

.:10.07.09.00142



ST M5-AG 4 MS-V

.:10.08.03.00311

Thread G1: M5-M

Material: Brass

Surface: nickel plated

Spring plunger

FSTIm M5-IG M5-IG A 5 VG-CO

Part no...:10.01.02.01620

<https://www.schmalz.ru/10.01.02.01620>



HTR-STA 47 1N D10/16 FL

.:10.08.03.00085

Length L: 47 mm

Connection 1: Sliding block

Connection of suction cup, spring plunger: Contour D10 and D16

Shape: flat



HTR-STS 30x30 D10/16 WI

.:10.08.03.00088

Connection 1: 30x30

Connection of suction cup, spring plunger: Contour D10 and D16

Shape: angled



HTR-STS 40x40 D10/16 WI

.:10.08.03.00089

Connection 1: 40x40

Connection of suction cup, spring plunger: Contour D10 and D16

Shape: angled