

# Basic Ejector


SBP-C 15 G02 NO A

Part no...:10.02.01.00626

<https://www.schmalz.ru/10.02.01.00626>


Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Generators > Basic Ejectors > Basic Ejectors SBP-C with Additional Functions > SBP-C 15 G02 NO A

## Basic ejector "BASE PUMP-controlled" with very light construction



|                                                        |
|--------------------------------------------------------|
| Nozzle diameter: 1.5 mm                                |
| Degree of evacuation: 85 %                             |
| Connection: G1/8"(1)-G1/8"(2)                          |
| Pressure optimal: 5 bar                                |
| Suction rate (max.): 71 l/min                          |
| Air consumption suction: 118 l/min                     |
| Control valve: Normally open                           |
| construction shape compact ejectors: Blow-off function |

## Design Data



| Attribute | Value    |
|-----------|----------|
| B         | 15 mm    |
| d         | 4.20 mm  |
| D         | 13.50 mm |
| G1        | G1/8"-F  |
| G2        | G1/8"-F  |
| G3        | G1/8"-F  |
| H         | 51 mm    |
| H1        | 50 mm    |
| H2        | 5.20 mm  |
| H3        | 8.50 mm  |
| L         | 106 mm   |
| L1        | 146 mm   |
| L2        | 19 mm    |
| L3        | 29.50 mm |
| SW1       | 14 mm    |
| SW2       | 14 mm    |
| X1        | 20 mm    |

## Technical Data

| Attribute | Value |
|-----------|-------|
|-----------|-------|

## Basic Ejector

SBP-C 15 G02 NO A

Part no...:10.02.01.00626

<https://www.schmalz.ru/10.02.01.00626>

|                                               |                 |
|-----------------------------------------------|-----------------|
| Nozzle diameter                               | 1.50 mm         |
| Degree of evacuation                          | 85 %            |
| Suction rate (max.)                           | 4.30 m³/h       |
| Suction rate (max.)                           | 71 l/min        |
| Air consumption suction                       | 7.10 m³/h       |
| Air consumption suction                       | 118 l/min       |
| Sound level free                              | 72 dB(A)        |
| Sound level suction                           | 65 dB(A)        |
| Pressure range (operating pressure)           | 3.0 ... 6.0 bar |
| Pressure optimal                              | 5 bar           |
| Recomm. internal hose diameter compressed air | 4 mm            |
| Recomm. internal hose diameter vacuum         | 6 mm            |
| Weight                                        | 70 g            |
| Operating temperature                         | 0 ... 50 °C     |
| Pressure range (operating pressure)           | 43.5 ... 87.0   |
| Pressure optimal                              | 72.50 psi       |
| Suction rate (max.)                           | 2.51 cfm        |
| Air consumption suction                       | 4.17 cfm        |
| Air consumption blow off                      | 1.06 cfm        |
| Product family                                | SBP-C           |

Note: The supply voltage for vacuum switches and solenoid valves is 24 VDC Air consumption: On version with solenoid valves SBP-C 07 (24) / SBP-C 25 (320) and optimal operating pressure Hose diameter: For max. length 2 m

## Accessories



### BEF-PL 110x44.5x3 SBP

Part no...:10.02.01.00511

Length L: 110 mm

Width B: 44.5 mm

Height H: 3 mm


Construction use: Basic ejector SBP

## Basic Ejector

SBP-C 15 G02 NO A

Part no...:10.02.01.00626

<https://www.schmalz.ru/10.02.01.00626>



### SET SBP M4-IG

Part no...:10.02.01.00769

Length L: 50 mm

Width B: 14 mm

Construction use: Basic ejector SBP

Type: M4-IG



### ASK B-MIC10 3000 K-2P

Part no...:21.04.06.00086

Material hose: PUR cable

Electrical connection: Connect. 10mm



### VFT G1/4-IG 80

Part no...:10.07.01.00119

Connection: G1/4"-F

Shape: Short filter insert

Nominal flow rate: 110 l/min

Nominal flow rate: 6.6 m<sup>3</sup>/h

Filter pore size: 80 µm

## Spare parts

### Contact Schmalz

OOO Schmalz | Mozhayskoe highway 165, bldg1, 121596 Moscow, Russia | +7 495 9671248 | [post@ruschmalz.ru](mailto:post@ruschmalz.ru)

## Basic Ejector

SBP-C 15 G02 NO A

Part no...:10.02.01.00626

<https://www.schmalz.ru/10.02.01.00626>



### SD G1/8-AG 14x40

Part no...:10.02.01.00540

Thread G1: G1/8"-M

External diameter D: 14 mm

Length L: 40 mm